

Chalk paint manual

Betonlook.nl's Chalk Paint is extremely suitable for painting various surfaces. E.g. walls, ceilings, stairs or furniture. The paint has a matt, even look.

Preparation non-flat surfaces

Tiles

Do you want to flatten a tiled wall? Sand it down with a diamond polishing machine first. You can then use plaster to flatten the wall. Remember to always use the Ardex R1C in wet areas and a gypsum-based plaster in dry areas.

Preparation flat surfaces

Furniture

Do you want to paint furniture or a wooden surface? Always make sure you first degrease the area and lightly sand it. You can then apply our EcoPrimer, to ensure good adhesion of the paint.

Walls

Is there a layer of coating on your wall or a waterproof paint? Always sand it down and apply our EcoPrimer before applying our Chalk paint. This makes sure the primer adheres to the surface properly.

If the wall does not have a previous layer of coating or waterproof paint, you don't need to sand it down. But you still need to apply the EcoPrimer.

Applying the paint

Step 1: always use a primer suitable for our paint before you start painting. When using our EcoPrimer, always allow it to dry for 12 hrs.

Step 2: check the sticker on the can and make sure it matches the colour you ordered. If it does, open the can and stir the paint well with a stirring rod.

Step 3: apply the first layer of paint. We recommend using a roller for this, but a brush will work just as well on smaller surfaces.

Step 4: wait at least 8 hrs for the first layer of paint to dry.

Step 5: apply the second layer of paint. For this you can also use a roller as well as a brush.

Step 6: wait for it to dry. If you've applied it on a surface that needs to be water resistant, we recommend adding a layer of our Concrete Ciré coating. For example: stairs, a kitchen backsplash, walls in your toilet/bathroom, tables or other furniture.

Shelf life

Chalk paint from Betonlook.nl has an unopened shelf life of 6 months, if you store it in a dry environment, at a temperature of between 10°C and 30°C.

Tips

- Paint the surface in one go. In contrast to our other products, Chalk Paint can easily be touched up. As long as the paint hasn't dried completely yet.
- Chalk paint can be applied in the bathroom and toilet as well, be sure to add a layer of our Concrete Ciré coating to make it water resistant. As it can't be made completely waterproof with this coating, we advise against using it in the shower area.